

Self-Leveling Rotary Laser Kit with GreenBrite® Technology

Model #: 40-6543
UPC: #049448065431
MSRP: \$1,565.42



Green Beam is 400% more visible than red beam, Self-leveling in the horizontal plane, Locking mechanism protects inner pendulum during transportation, Manual-leveling in the vertical plane with 90 degrees split beam, Laser beam modes include dot and two adjustable line lengths, Visual and audible alarms when beyond leveling range, 40-6543 Kit Includes > Laser, remote control with 9V battery, wall/ceiling mount, NiMH rechargeable battery pack, 4 "C" alkaline battery compartment (batteries not included), 6.4V battery adapter, tinted glasses, magnetic target, instruction manual with warranty card, hard-shell carrying case

PRODUCT DETAILS

40-6543 Kit Includes > Laser, remote control with 9V battery, wall/ceiling mount, NiMH rechargeable battery pack, 4 "C" alkaline battery compartment (batteries not included), 6.4V battery adapter, tinted glasses, magnetic target, instruction manual with warranty card, hard-shell carrying case

- Green Beam is 400% more visible than red beam
- Self-leveling in the horizontal plane
- Locking mechanism protects inner pendulum during transportation
- Manual-leveling in the vertical plane with 90 degrees split beam
- Laser beam modes include dot and two adjustable line lengths
- Visual and audible alarms when beyond leveling range



SPECIFICATIONS

Accuracy	+/-3/16"/100 ft. (+/-1.5mm/10m)
Battery Life	Approximately 16 hours with rechargeable battery pack; 15 hrs with alkaline batteries
Center Screw Thread	5/8"-11
Dimensions	7.087" x 6.378" x 7.953" (180x 162x202mm)
Exterior Range	Up to 1,200' diameter (365m) with detector (not included)
Interior Range	Up to 400' (120m) diameter depending upon light conditions
IP Protection Class	66
Laser Beam Modes	0, 30, 60 degrees
Laser Classification	Class IIIa
Laser Wavelength	532nm+/-10nm (Green)
Leveling Method	Self-leveling (Pendulum)
Maximum Power Output	Less than/Equal to 5mW
Power Supply	NiMH rechargeable battery pack and 6.4V adapter , 4 "C" batteries
Remote Range	Up to 200ft. (60m) diameter
Rotation Speeds	150, 200, 250, 300 RPM
Self-Leveling Range	+/- 3.5 degrees
Warranty	3 Year Warranty
Weight	4.40lbs. (2kg)
Working Temperature	32 degrees to 104 degrees (0 degrees celsius to +40 degrees celsius)

APPLICATION

The Johnson Level 40-6543 can be used for the following indoor applications; layout of interior walls, check door and window heights, acoustical/drop ceilings, layout warehouse racking, room additions, drywall installation, partition installation, squaring floor and wall tiles, installing sprinkler systems, align and plumb walls, level floors, metal stud and wood framers, level cabinets, level shelving and countertops.



For additional information on Johnson products, please contact
Customer Service at 888.953.8357 or service@johnsonlevel.com
www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.