



Features

- Wattage selectable at time of installation.
- Models shipped wired to highest wattage.
- Approved for horizontal mounting - right or left discharge.
- Fan purge circuit.
- Disconnect switch.
- Drywall depth embossments on back can.
- 18 gauge powder coated steel & extruded Aluminum front.
- Manual reset thermal limit.
- Steel block fin element.
- Propeller style fan blade: 1060 RPM motor; 100 CFM.
- Weight 6 lbs.
- Rough in dimensions: 9 1/4" Wide x 12 1/8" High x 3 5/8" Deep.
- Grill dimensions: 10" Wide x 13 1/8" High.
- Approved for wall or ceiling installation.
- Made in U.S.A.

Standard Models

MPG CATALOG NUMBER	MPG MODEL NUMBER	SELECTABLE INSTALLATION WATTAGE	MAX BTUs	VOLTS	MAX AMPS	LIST
TAMPERPROOF IN-BUILT DOUBLE POLE THERMOSTAT (40° - 100° TEMPERATURE RANGE)						
09962102	E3055T2DWB	750 or 1500	5120	120	12.5	332
09962202	E3058T2DWB	900 or 1800	6143	120	15.0	331
09962502	F3052T2DWB	1000 or 2000	6826	208	8.3	
09456902	F30522T2DWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	208	10.8	384
09962802	HB052T2DWB	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3	333
09457202	HB0522T2DWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	240	9.4	382
09963102	GB052T2DWB	2000	6826	277	7.2	338
TAMPERPROOF IN-BUILT SINGLE POLE THERMOSTAT (0° - 110° TEMPERATURE RANGE)						
09960602	E3055TDWB	750 or 1500	5120	120	12.5	313
09960702	E3058TDWB	900 or 1800	6143	120	15.0	315
09961002	F3052TDWB	1000 or 2000	6826	208	8.3	
09456302	F30522TDWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	208	10.8	363
09961302	HB052TDWB	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3	313
09456602	HB0522TDWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	240	9.4	348
09961602	GB052TDWB	2000	6826	277	7.2	315

Accessories

MPG CATALOG NUMBER	MPG MODEL NUMBER	DESCRIPTION	LIST
09969402	305EX8	1" EXTENDER	45
09969302	305EX16	2" EXTENDER	46
09969202	305EX32	4" SURFACE MOUNT FRAME	54

Note: Please see page 60 for custom color availability - add 10% to net heater cost.