Loading Dock Lights - Modular

Modular Lights





DKL-LED







⚠ WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Features

- 14" long, 18/3 conductor cord plugs into electrical junction box on arm
- On/Off switch & wire guard included with each light head
- Bulb included with all light heads except DKL-INC
- Imported to TPI specifications.
- DKL-LED-37 is compliant with ROHS 2 Directive (2011/65/EU), that of which includes the application exemptions outlined in Annex III of the directive.

Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	LIGHT HEAD TYPE	MAX WATTS	MAX LUMENS	AVE. BULB LIFE (HRS)	WT. (LBS)	LIST
04465602	DKL-INC	Incandescent	300	3,700	2,000	5	89
04465702	DKL-QH	Quartz Halogen	500	11,000	2,000	6	133
04708602	DKL-LED	LED	12	960	50,000	7	205
04881302	DKL-LED-37	LED	37	2,373	>30,000	5	356
04843302	DKL-FL	Fluorescent	55	3,000	10,000	7	206

Mounting Arms

MARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer,

and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go

The outer arm on 40VA & 60VA arms will swing 300° in horizontal plane & 210° in vertical plane



Features

- 1 ½" square, 11 gauge, steel tubing
- 3" x 5" x ³/₁₆" mounting plate attaches with (4) 3/8" bolts
- 5' long, 18/3 SJTW conductor cord and NEMA 5-15 grounded plug
- Made in U.S.A.

Standard Models

to www.P65Warnings.ca.gov.

MFG CATALOG NUMBER	MFG MODEL NUMBER	ARM LENGTH TOTAL # OF ARMS		WT. (LBS)	LIST
04465402	DKL-40VA-ARM	40"	2	18	139
04465502	DKL-60VA-ARM	60"	2	24	176
04465302	24-LDA	24"	1	11	109
04466102	40-LDA**	40"	3	18	188
04466202	60-LDA**	60"	3	24	218

^{**}Indicates heavy duty dock arms (Horizontal swing only, no vertical movement)

Loading Dock Arm Fan



Features

- 18" high velocity circulator, with 3 speed, 1/8 HP, 115V, 1phase permanently lubricated, totally enclosed, PSC motor
- Modular fan plugs into electrical outlet on arm
- Coated steel guards and aluminum blades.
- Imported to TPI specifications.

Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	CFM			AMPS	WT.	LIST
		HIGH	MED	LOW	HIGH	(LBS)	LIST
07971802	LDF-18-TE	1800	1500	1300	2.2	20	216

Note: Must be used with LDA (Heavy Duty) mounting arms.